#### UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

# MARK SCHEME for the October/November 2007 question paper

## 9702 PHYSICS

9702/31

Paper 31 (Advanced Practical Skills 1), maximum raw mark 40


This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

• CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the October/November 2007 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.



Page 2		Mark Scheme	Syllabus	Paper
		GCE A/AS LEVEL – October/November 2007	9702	31
Questic	on 1			
Manipu	ılation, m	easurement and observation		
Succes	sful colle	ection of data		
(a)	` '	meter of wire. 2 d.p. (mm) in raw data. Allow 0.195 or 0 9 mm – 0.02 mm or SV – 0.02 mm). Consistent unit. U		[1]
	(i) Rep	eat measurement		[1]
(c)	Five man Four ma Three m Major or Minor he micron Unreaso (e.g. Vol	irements in table rks for six sets of readings for V and I rks for five sets arks for four sets, etc. unspecified help 2 (e.g. setting up circuit) elp: 1 (e.g. minor changes with circuit) AND 1 (help veneter) anable values of V 1 tage values are the same ( $V_{max} = V_{min} < 0.5V$ ), wrong for if any one value of V < 0.5 V.)	•	[5]
Range	and distr	ibution of values		
(c)	(I <sub>max</sub> I <sub>m</sub>	<sub>in</sub> ) must be greater than or equal to 70 cm. Ignore POT	error.	[1]
Presen	tation of	data and observations		
Table: I	layout			
(c)	Each co Ignore u There m	headings: V/V; I/cm; I/A/m <sup>-1</sup> .  Iumn heading must contain a quantity and a unit where nits in the body of the table. Ignore POT errors. ust be some distinguishing mark between the quantity dus is expected, but accept, for example, I (cm)).		[1]
Table: ı	raw data			
(c)	All value	ency of presentation of raw readings es of I must be given to the same number of decimal pla 1 mm or 1 cm	aces.	[1]

Table: calculated quantities

(c) Significant figures. Apply to I/A.
I/A should be given to the same number or one more than the lowest number of significant figures from I or <u>raw</u> values of d.

(c) Values of I/A correct using candidate s figures. Allow small rounding errors.

Check a value. If incorrect, write in the correct value. Ignore POT error. [1]

[1]

<b>g</b>	GCE A/AS LEVEL – October/November 2007	9702	31
Graph: layout			
Sensil Scale: the gr	If wrong graph plotted (e.g. I against I/A) do not award mble scales must be used. Awkward scales (e.g. 3:10) are s must be chosen so that the plotted points occupy at lea aph grid in both x and y directions. Allow inverted axes. s must be labelled with the quantity which is being plotted	not allowed. st half	[1]
Graph: plottin	ng of points		
Ring	servations must be plotted. No blobs (points [ half a sma and check a suspect plot. Tick if correct. Re-plot if incorre to an accuracy of half a small square.	• ,	[1]
Graph: trend l	line		
Do no Judge There	of best fit. Allow 1 point off. At least 5 trend plots needed. It award mark if large scatter. It by scatter of points about the candidate's line. It must be a fair scatter of points either side of the line. It best line if candidate's line is not the best line.		[1]
Quality of data	a		
All plo	e by scatter of points about the best fit line. Allow up to – 0 otted points are assessed for this mark. st 5 plots needed. If V constant do not award mark.	).05V.	[1]
Analysis, con	clusions and evaluation		
Interpretation	of graph		
R ui	radient he hypotenuse of the must be at least half the length of lead-offs must be accurate to half a small square. Do not nless on the line of best fit. Write in correct read off. theck for y/ x (i.e. do not allow x/ y).		s [1]
Т	-intercept he value must be read to the nearest half square. he value can be calculated using ratios or y = mx + c. Inc a false origin has been used then label FO.	orrect algebra 1	[1]
Drawing conc	lusions		
` '	for k, 0.5 V Y k Y 2.5 V d be y-intercept. Unit required. 2 or 3 SF.		[1]
Must of 2 or 3			
Sensil	ble answer checked using candidate s figures into correct	substitution. m=	I [1]
			[Total: 20]

Mark Scheme

**Syllabus** 

Paper

Page 3

Page 4	Mark Scheme	Syllabus	Paper
	GCE A/AS LEVEL – October/November 2007	9702	31

#### Question 2

#### Manipulation, measurement and observation

Successful collection of data

(a) (iii) Position of end of rule at equilibrium. Nearest cm or mm. < 1m Consistent unit. [1]</li>
(b) First value of d between 1 and 5 cm. If lowest position given write in correct value of d. [1]
(b) First value of highest position within 5 cm of the equilibrium position. [1]
(d) Second value of d. Different value to the first. Allow out of range. [1]
(d) Second value of highest position. [1]
(d) Repeated measurements for highest position (evidence from (b) or (d)) [1]

Quality of data

(d) Bigger d gives bigger x. Check with corrected values of d and x.

If d < x in either case or if d = x in both cases, this loses the mark.

[1]

#### Presentation of data and observations

Display of calculation and reasoning

- (b) First value of x calculated correctly
  Calculation must be checked. Write down the correct value if answer wrong. [1]
- (d) Second value of x calculated correctly

  Calculation must be checked. Write down the correct value if answer wrong.

  [1]
- (e) Correct calculation to check proportionality ecf if candidates value of d is the lowest position. Possibilities include: two calculations of x/d ratio of x values and ratio of d values both calculated [1]

#### Analysis, conclusions and evaluation

Drawing conclusions

(e) Conclusion based on calculation. Consistent argument.
Incorrect ideas score zero. [1]

#### Estimating uncertainties

(c) Percentage uncertainty in x
Allow uncertainty in x; 2 mm Y x Y 10 mm.
If repeated readings have been done then the uncertainty could be half the range.
Correct ratio idea required x 100 stated/implied.

[1]

Page 5	Mark Scheme	Syllabus	Paper
	GCE A/AS LEVEL – October/November 2007	9702	31

### Identifying limitations

- (f) (i) Relevant points must be underlined and ticked. Some of these might be:
  - **A** Only two readings (are not enough to draw a valid conclusion).
  - **B** Hard to judge/see (when/where) <u>highest position</u> with reference to movement. Do not accept reaction time ideas.
  - **C** Parallax (error) or good diagram demonstrating this.
  - **D** Difficulty in release/keeping rule still prior to release (reference to force).
  - **E** Equilibrium position changes with evidence shown in measurements.
  - **X** Other additional source of error.

[4]

## Suggesting improvements

- **(f) (ii)** Relevant points must be underlined and ticked.4 Some of these might be:
  - A Take more readings and plot a graph/calculate k values.
  - **B** High speed (camera to take) photographs/film the motion and <u>play back</u> frame by frame/ slow motion/ use pause OR motion/position sensor above/ below mass OR trial and error with light gate/ horizontal marker.
  - C Measure at eye level/repeat to get eye in right place/ place rule as close as possible to vertical rule/use helper to release or measure/use mounted pin at end of rule (to help locate position on scale).
  - **D** Use a named method to release the rule e.g. cotton and candle or scissors/electromagnet/end stop or clamp.
  - **X** cm rule use a mm rule. Need to see evidence in their previous measurements that their readings are taken to the nearest cm or 0.5 cm.
  - Y Other additional solution, well explained.

Do not allow repeated readings, vacuum, draft free room Do not allow use a computer to improve the experiment

Do not allow increase range/change load on ruler/change length of ruler/changing quality of ruler [4]

[Total: 20]